



Cement-, Mortar-, Screed topping-, Gypsum- and Aditive testing

BASIC

Automatic Vicat needle device


- Easy control over a weather-proof membrane keyboard with 6 control buttons.
- LCD-display for reading the test standard and residual time.
- Indication recording built in up over writing reel.

Technical features:

Fix programmable test geometries according to the standards:

- EN 196 - stiffness begin
- EN 196 - stiffness end
- EN 196 - standard shore
- EN 13279-2, EN 14496, DIN 1168-2
- EN 480
- free programmable plunge-in times: 15-99 sec.
- free programmable holding times: 15-9999 sec.
- It can be safed 20 test operations consists of: test geometrie-penetrations, plunge-in and holding times.

Delivery range:

- Order no. B 26660: for tests on cement acc. to EN 196-3
- Order no. B 26662: for tests on cement acc. to ASTM C 191
- Order no. B 26664: for tests on building plaster acc. to EN 13279-2, EN 14496, DIN 1168-2
- Order no. B 26666: for tests on additive acc. to EN 480-2
- Order no. B 26668: for tests on cement acc. to EN 196-3 and for tests on additive acc. to EN 480-2
- Order no. 26670: autom:  er



FORM+TEST Seidner & Co. GmbH

Zwiefalter Str. 20 • D-88499 Riedlingen
phone: +49 (0) 7371 9302-20 • fax: -99
www.formtest.de
sales@formtest.de